

"Products designed with SECURITY in mind"
SECURCOMM
BY DC SECURITY PRODUCTS

DOWNLOADER DL110 UNIVERSAL DATA DOWNLOADING MODEM

In an effort to supply the security industry with state-of-the-art equipment designed for the rigors of everyday usage, Securcomm presents the universal **DOWNLOADER DL110**. This **AC / DC POWERED** modem is the first downloading modem created to incorporate the latest advancements in modem technology with the programming flexibility required for the many Security Control Panels on the market today. The **DOWNLOADER DL110** has been designed to download information at rates of **2400bps** to **110bps** and below. The **DL110** provides these special modem data baud rates, which are becoming increasingly unavailable in modems on the market today. This means more universal performance, greater features, increased productivity, higher reliability and the best value for your Computerized Alarm Panel Installation applications. Our Securcomm Model **DL110** provides a complete implementation of the **BELL 212** and **103** standard for modem operation. The **DOWNLOADER DL110** was created to provide the slower data speeds and the information throughput needed for the many of the newer as well as the older existing brands of ITI®, Radionics®, Detection Systems®, Caddx®, Ademco®, Moose®, C&K®, Scantronics®, Paradox®, DSC®, Liner®, Rokonet®, and many other Control Panel models on the Security Market.

PRODUCT SPECIFICATIONS

DATA COMPATIBILITY:

◆ DL110:

- V.22A&B, V.23, V.21, BELL 212A,
- BELL 103J.

DTE INTERFACE:

◆ DL110:

- V.24 (RS-232-C).
- Asynchronous and synchronous.
- Autobaud or selectable formats.

LINE INTERFACE:

- Line type 2 wire dialup.
- Transmit level -10dBm.
- Receive sensitivity -6 to -43dBm.
- Dial signaling Pulse/DTMF.

AUTO DIAL MODES:

- AT compatible.

POWER:

- Standard 9VAC or 9-14VDC.

POWER CONSUMPTION:

- 259ma 12vdc / 3.1w AC

PHYSICAL:

◆ DL110:

- Length 5.02 inches.
- Width 5.02 inches.
- Height 1.47 inches.
- Weight 12 ounce

ENVIRONMENTAL:

- Temperature 0 - 60 C.
- Humidity 90% non-condensing.

APPROVALS:

- FCC Part 68.
- FCC Part 15, Class A.



**GET UNIVERSAL
CONNECTION...**

GET SECURCOMM DL110!!!

**DC SECURITY
PRODUCTS, INC**

ONE LINDSAY CIRCLE
SAN FRANCISCO, CALIFORNIA 94124
Voice (415) 550-0443 Fax (415) 550-1780
www.dcsecurityproducts.com